

LTA-450

Teller Cash Recycler ATECAP



CUSTOMIZED SERVICE CONCEPTS, LLC

OPERATIONAL FEATURES

- Up to 12 denominations recycling (Multi country currency)
- Up to 22,800 notes of storage capacity
- Operational (transit) cassette is available inside safe for secure note loading and unloading
- Optimally configurable cassette options based on various demands in capacity/denomination
- High precision banknote recognition of images, patterns, etc.
- Unattended self-audit and notes loading/unloading without exposure of operational (transit) cassette

UNIQUE FEATURES

- Up to 600 notes of rejected notes or physical escrow capacity
- Automatic retract of untaken notes
- Use as desktop note counter, then automatic deposit of counted notes from output pocket
- Entire note path is located outside of safe for increased safety and easy maintenance
- Serial number and currency image recording
- Largest recycling capacity
- Internal secure transit cassette

BEST IN CLASS SECURITY

- Accurate counterfeit notes recognition and 'sort out'
- Note serial number recognition and image capture
- Equipped with international standard certified safe
- Reporting of "duress" note dispense serial numbers and note images

HIGH EFFICIENCY

- Smallest footprint
- 8" foldable touch screen
- On screen operator training and guidance videos

LTA-450 Specifications

Main Control Unit	Intel, Memory 4G, SSD 125G, Windows 10		
User Interface	8" wide LCD with touch screen		
Cash Recycling Module	Denominations	Max. 12 denomination (by split CST 6EA)	
	Transaction speed (Deposit/Dispense)	10 ~ 12 notes/sec	
	Cassette capacity**	Recycling CST	Large CST (3,800 notes) up to 6 EA, mixed with split CST
			Split CST (1,500 + 1,500 notes) up to 6 EA, mixed with large CST
		Operation CST	3,800 notes
		Max Total	22,800 notes
	Deposit hopper max. capacity	500 notes, continuous feed	
	Withdrawal hopper max. capacity	300 notes/transaction	
	Retract/reject hopper max. capacity	100 notes	
	Reject notes/physical escrow	Max. capacity 600 notes	
Dimensions	Size (W x H x D)	UL291: 15" x 31.25" x 44"	
	Weight	UL291: 1,058 lbs.	
Safe Certification	UL291, CEN-III, CEN-IV		
Safety (Lock)	Dial lock (option: electronic or key lock)		
Security Alarm (Optional)	Shock/vibration sensor, heat detection sensor		
Environmental Conditions	Operation	+5°C to +40°C	
		25% to 85% relative humidity	

*Specifications are subject to change without prior notice for product improvement.

**Cassette capacity: Based on 0.01cm thickness note

Customized Service Concepts, LLC.

18 Cote Ave, Suite 13
Goffstown, NH 03045



51 Ozick Drive, Suite 101
Durham, CT 06422

800-341-8641

CSCATM.COM

FOLLOW US!

